



Specification:

Heavy-duty hydraulic jacks of the ECO-Jack XR series do, compared with the ECO-Jack S-series, require an external 700 bar pump for operation. This facilitates and accelerates working in confined conditions and when using several jacks at the time. The compact design without a pump leads to a weight reduction of up to 30% and allows for easy handling for optimal use under extreme conditions. External pumps allow simultaneous operation on several ECO-Jack XR series machine jacks by one person. The ECO-Jack XR series has an integrated spring return system, which always returns the machine lifter automatically to the starting position.

Technical data of hydraulic jacks:

#	01 230 31 01	700 bar	600 ml	61 kg
HH	155 mm	23000 kg	18400 kg	
3 x 100 mm		20 mm	External pump	
			L x B x H 269 x 392 x 330 mm	

Please always observe the operating instructions, their safety instructions and local conditions!

#	Part No.	Maximum operating pressure in bar	Oil quantity in the tank / cylinder in ml. Standard oil HLP 32 other oils on request	Weight kg	Dimensions in mm L x B x H
HH	Adjustment positions Distances in mm	Maximum stroke in mm	Maximum lifting load with the lifting head in kg	Maximum lifting load with lifting claw in kg	
3 x 100 mm	Insertion height in mm		Stroke in mm with SH (fast stroke) and NH (normal stroke)		